


3-Way Power Splitter

BX-PS-03-43F
380–3800 MHz | 4.3-10 Female | IP65



3D View



Block Diagram

Electrical Specifications

Frequency range	380–3800 MHz	
Number of output ports	3	
Insertion loss	≤ 5.3 dB	380–3800 MHz
VSWR	≤ 1.20 (typ. 1.15)	380–3800 MHz
Return loss (all ports)	≥ 21 dB (typ. 23 dB)	380–3800 MHz
PIM (IM3), 3rd order @ 900 MHz, 2 × 20 W	≤ -160 dBc (typ. -163 dBc)	
Impedance	50 Ω	
Total input power	400 W average	

Mechanical Specifications

Connectors	4.3-10 Female	IEC 61169-54
Dimensions (L × W × H)	350 × 25 × 25 mm	Excl. connectors
Weight	0.65 kg	
Color	Black	
Mounting	Wall / Mast	Brackets sold separately


Environmental Conditions

Degree of protection	IP65	Indoor/outdoor
Operating temperature	–35 °C to +75 °C	
Relative humidity	5% – 95%	Non-condensing

All specifications are guaranteed minimums per ST 625.10 (DAS passive components) under stated test conditions, unless otherwise noted.

Mechanical Drawing


All dimensions in mm. Tolerances: ±2 mm unless otherwise stated.



Standard: 4.3-10 female (50 Ω): IEC 61169-54

modifications reserved!

Block Diagram



Ordering Information

Part number	Description	Connectors	Mounting
BX-PS-03-43F	3-Way Power Splitter, 380–3800 MHz	4.3-10 Female (all ports)	Brackets sold separately

Accessories	Description
BX-TL-050-43M	Termination Load 50 W (for unused ports)

Specifications subject to change without notice. All values are guaranteed minimums unless stated otherwise. BDC products are designed, specified, and validated by Bandercom Oy — a DAS/IBS contractor with 15+ years of field experience. Contact: info@bander.com | www.bander.com